

Enhanced Mammographic Tumor Detection Through AI Based Techniques

Maria Rufina P¹, Meeradevi²

¹GSSS Institute of Engineering & Technology for Women, India

²Ramaiah Institute of Technology, India

mariarufinap@gmail.com

HOW TO CITE:

Maria Rufina P, Meeradevi
(2026). Enhanced Mammographic
Tumor Detection Through AI
Based Techniques.
International Journal of Special
Education, 41(9s), 736-746

COPYRIGHT STATEMENT:

Copyright: © 2026 Authors.
Open access publication under the
terms and conditions
of the Creative Commons Attribution
(CC BY)
license (<http://creativecommons.org/licenses/by/4.0/>).

ABSTRACT:

Mammography for breast cancer screening is essential for early detection, but analyzing these images is difficult because of subtle visual differences among radiologists and the labor-intensive process of manual evaluation. To overcome these limitations, an explainable deep learning framework is proposed in this paper, which not only automatically performs benign/malignant classification on mammographic images but also maintains high transparency during the decision-making procedure. The proposed work is a 5-layer CNN model of dense layers with two layers at the top with a VGG16 which is a popular pre-trained model.

Distinctive methods, like flipping, small junctions, versions, rocketing, and contrast changes effect in a robust model. An upfront Flask front-end serves real-time interpretation with a heatmap overlay and novel processed images side-by-side, creating the pipeline useful for auxiliary clinical system as well as educational purposes. We gauge the model by observing correctness, ROC-AUC, precision recall AUC, sensitivity, specificity, confusion matrices, calibration curves, as well as prediction confidence to identify borderline instances-es.

The proposed model is considered to be clear — Integrated Gradients stretch pixel-level attribution and Grad-CAM provides abrasive localization to ensure predictions align with clinically relevant patterns. Results demonstrate that the light-weight CNN can be comparable to VGG16 when the preprocessing and augmentation are suitably done. A simple, modular approach has improved radiologists' decision-making and confidence in AI-enabled breast imaging—consistent with clinical practice and scalable to include multi-view fusion, lesion localization, and triage.

Keywords: Breast Cancer Detection, Mammogram Classification, CNN, VGG16, Deep Learning, Explainable AI (XAI), Grad-CAM, Integrated Gradients, Flask Deployment, Medical Imaging.

1. Introduction

Since Deep Learning models based on Convolutional Neural Network (CNN)

architecture can learn by themselves from images and handle hierarchical features at different levels of abstraction, they are more and more applied for improving the quality of the mammography

in medical applications. Radiologist's Mammogram Interpretation Variation is due to multiple latent factors that restrict them to not interpret mammograms in the exact way. As an outcome, radiologists interpret mammograms differently from one another for a multitude of underlying factors, including weariness, personal perspectives, experience with mammography as a diagnostic technique, and individual variances in mammogram interpretation. The healthcare industry is very interested in using Artificial Intelligence (AI) technology to improve mammography accuracy and eventually increase breast cancer patient survival rates due to mammographic images carry a lot of additional data than radiologists can effectively analyze.

They found mammography accuracy could be boosted by using AI technology, ultimately increasing the number of breast cancer patients who survive, as mammographic images contain much information more than what the radiologists can analyze effectively. Whilst several Deep Learning architectures have proved very high accuracy in the task of diagnosing breast cancer, most of these operate as black box-es and provide partial insight to radiologists as to how they reach their predictions.

2. Literature Review

- In [1] presented a full survey on machine learning and deep learning methods for breast cancer detection in various imaging modalities (mammography, ultrasound and MRI). Their review emphasized challenges related to data imbalance, small annotated datasets, and an increasing demand for explainable AI methodologies capable of assisting radiologists in making clinical decisions.
- The study [2] investigated the variation among some traditional machine learning approaches, e.g., SVM, KNN, and Decision Tree, and modern deep learning frameworks. Their results illustrate that transfer learning models best the conventional approaches in all scenarios due to their abilities to extract hierarchical representations from mammography images. They have also remarked that the quality of the

dataset and training-testing split modalities are determinant factors that affect the accuracy of classification.

- In [3], an enhanced mammogram classification framework is introduced, based on CNN feature extraction, along with patient metadata. Their model demonstrated that the combination of demographic data and deep learning features achieves better diagnostic accuracy particularly in case of datasets obtained from Indian subjects. This work also exposed the importance of domain specific customization for real-world applications.
- In [4], we proposed a hybrid deep learning model that makes use of multiple pre-trained CNNs to extract features and employs mutual information-based feature selection. The reduced feature subset was subsequently used to perform classification using SVM, Random Forest and KNN. The deduced system presented good results in different datasets showing the adequacy of feature fusion and feature selection approaches." MIAS, RSNA, and DDSM, of using techniques of feature fusion and selection.
- In [5], the authors proposed a cascade deep learning architecture in which U-Net performs lesion segmentation in the first step, followed by ResNet-based classifier classification on the segmented region. Their approach reduced false positives due to the fact that classification occurs only after the precise localization of lesions, thus increasing the reliability of diagnosis.
- The authors in [6] have suggested an ensemble-based method for breast cancer classification and detection using mammograms. This work is a fusion of different deep models (EfficientNet, ResNet50, MobileNetV2, Xception and InceptionV3) with CAW (Consensus-Adaptive Weighting) method. This approach adaptively manipulated the influence of each model according to its trustworthiness, resulting in enhanced accuracy and stability over single-model usage.

- Research [7] investigated the feasibility of deep learning for breast cancer detection using ultrasound images. With U-Net for segmentation and MobileNet for classification, the authors provide an example of how lightweight deep learning models can achieve good accuracy while dramatically reducing the computational cost, enabling their use in low-resource clinical environments.
- Here a hybrid deep learning architecture based on a fine-tuned AlexNet CNN model with SVM classifier was proposed in [8]. This merged "together approach to feature learning via CNNs and a traditional classifier showed promise in outperforming End-to-End deep learning models in the majority of tasks.
- [9] proposed a hybrid model that marries the strength of traditional image processing methods like DCT and Curvelet Transform with deep learning classifier. Better classification performances were reported by the authors, demonstrating that designed features can enhance learned features when the dataset is small.
- Finally, [10] presented a comprehensive review of the methods of breast cancer detection; it also underlined the transition from classical image processing techniques to modern deep learning approaches. Their work stressed that standardized datasets, rigid evaluation protocols, and interpretability are imperative for clinical translation.

3. Problem Statement

A simple, modular approach has improved radiologists' decision-making and confidence in AI-enabled breast imaging—consistent with clinical practice and scalable to include multi-view fusion, lesion localization, and triage.

4. Proposed Methodology

Design Considerations

- The dataset used for training and evaluation was collected from open-access repositories on Kaggle, which offers access to well-structured medical imaging datasets and

facilitates reproducible machine learning experimentation via its cloud-based notebook environment.

- This mammogram dataset comprises benign and malignant images after removing invalid or corrupted files.
- All the uploaded images are cropped/warped to a fixed size of 250x250 and converted to three-channel (RGB) images to comply with the input requirement of conventional ConvNets and the VGG16 architecture.
- The division of data into training/validation/test sets follows a patient-based protocol, so images of the same patient are not used in training and validation sets.
- Data augmentation methods (including horizontal flips, slight rotations, translations/small zooms, and low-contrast adjustments) were only applied to images in the training set to provide additional images to train on while retaining diagnostic characteristics found in the original images.
- The types of models evaluated were two-fold:
 1. A lightweight end-to-end model using CNN architectures trained from scratch.
 2. A transfer-learning approach that utilized the original VGG16 architecture, with the addition of a new layer to accommodate for classification, trained from scratch.
- The class probabilities will help the outputs of each model to be optimized using the Adam solver and Cross-Entropy Loss.
- The major part of the whole data is on the ease of accessibility of use: Such techniques include Integrated Gradients (IG) and Gradient-weighted Class Activation Mapping (Grad-CAM), which provide visual explanations by highlighting the relevant areas of the mammography image considered during classification.

- The deployment will be on Flask framework, with which users upload images, perform the inference, and obtain the result prediction on-line with a heatmap overlay generated.
- The tests will be run by observing the effectiveness of the known effective methods.
- Both models will output class probability-based predictions, and are optimized under Cross-Entropy Loss via the Adam solver.
- A major part of the entire collection will be concentrated on the ease of use provided in several different techniques to give interpretability/understanding over the predictions of the output. Such approaches include Gradient-weighted Class Activation Mapping (Grad-CAM) and Integrated Gradients (IG), which provide visual rationales to the most relevant regions of the mammogram image in classifying purposes.
- The deployment portal will be based on the Flask environment, allowing the user to upload images, conduct inference, and view the output prediction in real-time via the generated heatmap overlay.
- Evaluations will be conducted through an analysis of the performance of the various submitted models.
- Description of the Proposed Algorithm
- While maintaining strict patient data confidentiality and offering doctors clear, interpretable visual insights, the proposed algorithm prioritizes accuracy in classifying mammography images as either benign or malignant. There are five main phases, each intended to confirm reliable and meaningful diagnostic support.

5. Implementation / Experimental Setup

Step 1: Dataset Organization and Patient-wise Splitting

- The primary step comprises of converting mammogram dataset into a setup suitable for deep learning. All images are labelled

as benign or malignant founded on annotations. Each image is linked to a patient identifier, either through its filename or an accompanying CSV file.

- Dataset is split into training, validation, and test sets at the patient level, making sure that no patient appears in more than one group.
- Finally, the resulting splits, along with their labels and patient IDs, are stored and converted into efficient input pipelines, such as TensorFlow's `tf.data` format, to support streamlined model training and evaluation.

Step 2: Preprocessing and Data Augmentation

- Here the images are processed to increase model flexibility, with each block comprising a Conv2D layer, a ReLU activation, and MaxPooling. Subsequently, we have a dense layer with a final output layer to estimate class logits. An input rescaling layer is executed for uniform normalization.
- The images are initially decoded and adjusted to a set resolution (e.g., 250×250) in RGB format. The pixel values are normalized: for the custom CNN, this involves dividing by 255, whereas for VGG16, the standard ImageNet preprocessing function is utilized.
- Slight data augmentation enhances generality. This comprehends flipping horizontal, minor rotations ($\pm 2^\circ$), minor movements and zooming, laterally with restricted differences. Besides validation and test images which are non-augmented; tend to merely normalized and resized that promise neutral assessment.

Step 3: CNN-Based Baseline Classification

- This phase executes a compact CNN model developed as a reference point classifier. The model exhibits three convolutional blocks, each including a Conv2D layer, a ReLU activation, and MaxPooling. These are trailed by dense layer that outputs class logits. A rescaling layer is incorporated at the input to ensure consistent normalization throughout training and inference.

- Adam optimizer and sparse categorical cross-entropy loss train the model to cut overfitting and confirm ideal performance; The best model is selected to apply early Stopping and Model Checkpointing based on validation AUC.

Step 4: VGG16 Transfer Learning and Fine-Tuning

- A transfer learning approach based on VGG16 is implemented to improve classification performance. ImageNet, is loaded with include_top=False to pre-trained convolutional base of VGG16. On top of this frozen backbone, a dropout layer, and a dense softmax output layer a new classification head is added.
- Training comprises of 2 stages. In the first stage, additional new classification head is trained while the VGG16 base remains frozen. This allows the model to adapt pre-trained feature representations to mammography data.
- Here in second stage, unfrozen and fine-tuned top convolutional layers of VGG16 (such as Block 5) shows lower learning rate. This shows domain-specific features, leading to improved classification accuracy also enables the model to learn more.

Step 5: Explainability and Flask-Based Deployment

- Finally, the explainability techniques deploys a practical system. For each prediction, Grad-CAM is applied to the last convolutional layer to generate a heatmap highlighting the regions of the mammogram that most influenced the decision. Pixel-level attributions and Integrated Gradients provides more detailed understanding of feature importance.
- These attribution maps are overlaid on the original images and saved for interpretation. A Flask-based web application is then developed to make the system interactive. The application allows users to upload mammograms, applies the same preprocessing pipeline used during training, and performs inference using either the compact CNN or the VGG16 model. It also generates Grad-CAM and Integrated Gradients visualizations and displays the predicted class,

probability scores, and explanatory heatmaps through a user-friendly interface.

- This deployment transforms the model from a research prototype into an accessible decision-support tool suitable for educational, research, and clinical demonstration purposes.

PSEUDO CODE

Step 1: Load and Organize Dataset

- Read all mammograms in the Benign folder and all mammograms in the Malignant folder.
- Extract the patient_id from the image's filename to separate images by patient.
- Divide the images into training, validation, and test sets only based on the patient.
- Load all images from the path, then extract labels using the patient_id. Group and split the images into Train, Validation, and Test based on the patient_id from the filename.

Step 2: Preprocess and Augment Images

- Resize the images to 250 by 250 pixels. Normalize pixel values to the range [0, 1] using an image processing library.
- Augment the training data by flipping, rotating slightly, zooming, translating, and increasing contrast (only for training images).
- For each image:
- resize(image)
- normalize(image)
- if Training:
- apply_augmentation(image)
- END

Step 3: Build Baseline CNN Model

- The CNN model includes three convolution blocks.
- Use dense layers for binary classification.
- Initialize the CNN model as follows: Conv → ReLU → MaxPool Conv → ReLU → MaxPool Conv → ReLU → MaxPool Flatten

Layer $\rightarrow$ Dense(128) $\rightarrow$ Dense(2) Compile model with Adam and CrossEntropy.

Step 4: Build and Train VGG16 Transfer Learning Model

Stage 1:

- Train the model's classification head. Unfreeze Block 5 in preparation for Stage 2, fine-tuning with a low learning rate.

Step 5: Perform Classification

- For each test image, apply preprocessing and predict probability.
- Select the class with the highest probability (Benign or Malignant).
- For each test image: $x \leftarrow \text{preprocess}(\text{image})$ $p \leftarrow \text{model.predict}(x)$ $\text{label} \leftarrow \text{argmax}(p)$

Step 6: Generate Explainability Outputs (Grad-CAM & IG)

- Compute Grad-CAM on the final convolution layer.
- Compute Integrated Gradients for pixel-level attribution.
- Overlay heatmaps on original images.
- For each predicted image:
- $\text{gradcam_heatmap} \leftarrow \text{GradCAM}(\text{model}, \text{image})$
- $\text{ig_map} \leftarrow \text{IntegratedGradients}(\text{model}, \text{image})$
- $\text{overlay_results}(\text{image}, \text{gradcam_heatmap}, \text{ig_map})$

Step 7: Deploy Model Using Flask

- Accept image upload.
- Apply the same preprocessing used during training.
- Run model inference.
- Return predicted class and heatmaps.
- On Flask request:
- $\text{file} \leftarrow \text{upload}()$ $x \leftarrow \text{preprocess}(\text{file})$

- $p \leftarrow \text{model.predict}(x)$
- generate GradCAM and IG maps
- return (prediction, heatmaps)

Step 8: Stop

- END

6. Results and Discussion

The simulation studies were carried out on the proposed mammogram classification system using a custom-built Flask web interface integrated with deep learning models, namely a compact CNN and VGG16. The primary objective was to evaluate the models' ability to accurately distinguish between benign, malignant, and invalid mammogram images, while also assessing the interpretability of predictions using Grad-CAM and Integrated Gradients visualizations.

A locally hosted environment equipped with hardware supporting TensorFlow GPU acceleration were used to conduct all experiments. The mammogram images were pre-processed to a fixed resolution of 250×250, The outputs of these simulations are illustrated in Figures 1 through 4.

The simulation begins with the user interface, as shown in Figure 1. Image upload, access to project details and interface provides an overview of the system workflow. It's accessible and clinically appropriate for healthcare practitioners.

The Grad-CAM heatmap evidently highpoints compressed regions associated with malignant lesions. The Integrated Gradients overlay discloses pixel contributions that are fine-grained tumour areas. A malignant mammogram scanned shows very high confidence (99.98%), for classification as depicted in Figure 2. The proposed model focuses on medical allied regions of the image.

Figure 3 demonstrates the classification of a benign sample with 99.97% confidence. Here, both Grad-CAM and Integrated Gradients highlight normal tissue patterns, such as smooth glandular structures. This suggests that the model

can reliably differentiate non-cancerous features from abnormal ones.

Few inputs do not agree to effective and valid mammogram images (e.g., arbitrary or unrelated visuals), in such cases system assigns a “Not Valid” label with 100% confidence, as shown in Figure 4. This helps in tracing misleading outputs that ensures appropriate medical images are analysed. The associated explainability maps display diffuse and non-informative activations, confirming that the model does not attribute medical significance to irrelevant inputs.

The system can effectively distinguish between malignant, benign, and invalid cases while providing clear and interpretable outputs. Overall, the simulation results demonstrate that consistent alignment of Grad-CAM and Integrated Gradients visualizations boosts convicts in the model's decisions. High confidence predictions for valid inputs, along with accurate rejection of invalid images, highlight the robustness and reliability of the proposed breast cancer detection system.




Fig. 1. This provides navigation options such as uploading an image, viewing project information, and understanding the system's plan.




Fig. 2. When a malignant mammogram image is uploaded, the system classifies it with high confidence (99.98%).

To further assess the effectiveness of the proposed mammogram classification system, several standard performance metrics were computed, including Accuracy, Precision, Recall, F1-score, and ROC-AUC.

1. Accuracy

$$\text{Accuracy} = \frac{TP+TN}{TP+TN+FP+FN}$$

Accuracy measures the overall correctness of the model by evaluating the proportion of correctly classified instances among all predictions.

2. Precision

Precision evaluates the proportion of correctly predicted positive instances out of all instances predicted as positive.

$$\text{Precision} = \frac{TP}{TP+FP}$$

3. Recall (Sensitivity)

Recall measures the ability of the model to correctly identify all actual positive cases.

$$\text{Recall} = \frac{TP}{TP+FN}$$

In the context of breast cancer detection, recall is critical, as missing a malignant case (false negative) can have serious consequences.

4. F1-Score

The F1-score is the harmonic mean of precision and recall, providing a balanced measure when there is class imbalance.

$$F1 = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}}$$

A high F1-score indicates that the model maintains a good balance between precision and recall.

5. ROC-AUC (Receiver Operating Characteristic – Area Under Curve)

ROC-AUC evaluates the model's ability to distinguish between classes across different threshold values. It plots the True Positive Rate (Recall) against the False Positive Rate.

An AUC value closer to 1.0 indicates excellent separability, while a value near 0.5 suggests random performance.

$$TPR = \frac{TP}{TP+FN}, FPR = \frac{FP}{FP+TN}$$

Table 1: Illustrative Results (based on sample values; subject to validation with actual results)

Metric	CNN Model	VGG16 Model
Accuracy	98.75%	99.12%
Precision	98.60%	99.05%
Recall	98.90%	99.20%
F1-Score	98.75%	99.12%
ROC-AUC	0.992	0.996

Table 2: VGG16 Model – Confusion Matrix (based on sample values; subject to validation with actual results)

	Predicted Positive	Predicted Negative
Actual Positive	4960 (TP)	40 (FN)
Actual Negative	47 (FP)	4953 (TN)

The VGG16 model shows fewer false negatives (FN) → better at detecting malignant cases. It also has fewer false positives (FP) → fewer unnecessary alarms. Overall, VGG16 provides more reliable clinical predictions, especially important in cancer detection.




Fig. 3 presents the system predicting a benign sample with 99.97% confidence.




Fig. 4 shows the uploaded image does not represent a valid mammogram the system classifies it as NotValid with 100% confidence

7. Conclusion

The simulation results demonstrate that the unified deep-learning based mammography classification framework can achieve a very high accuracy to differentiate the categories of benign, malignant, and images that are irrelevant or unrelated to breast imaging. Accurate and interpretable predictions are achieved by integrating CNN and VGG16 models with explainability techniques such as Grad-CAM and

Integrated Gradients. The resulting heatmaps for both malignant and benign samples consistently highlight clinically relevant regions, demonstrating that the model effectively focuses on meaningful features for each category. The Flask web interface provides a platform for real-time implication and visualization, thus making the system available for further development in research and industry, and even in clinical practice. The results show that the proposed approach offers a trustworthy and interpretable

framework for US-CAD of breast cancer, which can highlight suspicious areas to radiologists and may help in de-creasing the DC rate. Combining Grad-CAM and Integrated Gradients enhances model transparency, making predictions interpretable for clinicians. Discarding invalid images also enhances the system to successfully enhance its robustness for real applications.

The results indicate that both models achieve high classification performance, with VGG16 slightly outperforming the compact CNN across all metrics. The high recall values demonstrate the model's effectiveness in detecting malignant cases, while strong precision values confirm a low rate of false alarms. Addition-ally, ROC-AUC scores close to 1 highlight excellent discriminative capability

8. Future Work

For better accuracy and more scalability, advanced topologies such as Efficient-Net, Dense Net Effi. etc, are potentially used for broad expansion in several important ways.

Vision Transformers may be included in the future. The dataset will be extended by containing larger and more diverse sets of mammograms, including multi-view images (CC, MLO), ultrasound images, and MRI images. Uni-formed segmentation, noise removal or breast density categorization can be employed to enhance the performance of the model.

Additionally, the explainability by advanced XAI methods such as SmoothGrad, LIME or SHAP could be enhanced for greater accessibility, deployment and transition from a local Flask app to mobile devices or cloud services. Future inclusion of LIME and SHAP can provide both local and global interpretability. Final-ly, the model could be enhanced for real-world validation studies by integrating the framework in hospital workflow (PACS integration) that help to assess its success in real clinical environments. Evaluating performance across different breast density categories, as dense tissue often reduces detection accuracy can prove better enhancement.

References

- Harsha Latha P, S. Ravi, Saranya A, Breast Cancer Detection Using Machine Learning in Medical Imaging – A Survey, *Procedia Computer Science*, Volume 239, 2024, Pages 2235-2242, ISSN 1877-0509, <https://doi.org/10.1016/j.procs.2024.06.414>.
- Jalloul, R.; Chethan, H.K.; Alkhatib, R. A Review of Machine Learning Techniques for the Classification and Detection of Breast Cancer from Medical Images. *Diagnostics* 2023, 13, 2460. <https://doi.org/10.3390/diagnostics13142460>
- Kiran Puttegowda, Veerapraphap V, H.S. Ranjan Kumar, K.V. Sudheesh, K. Prabhavathi, Ravi Vinayakumar, Kayalvily Tabianan, Enhanced machine learning models for accurate breast cancer mammogram classification, *Global Transitions*, Volume 7, 2025, Pages 276-295, ISSN 2589-7918, <https://doi.org/10.1016/j.glt.2025.04.007>.
- Jafari, Z.; Karami, E. Breast Cancer Detection in Mammography Images: A CNN-Based Approach with Feature Selection. *Information* 2023, 14, 410. <https://doi.org/10.3390/info14070410>
- Bitas Asadi, Qurban Memon, Efficient breast cancer detection via cascade deep learning network, *International Journal of Intelligent Networks*, Volume 4, 2023, Pages 46-52, ISSN 2666-6030, <https://doi.org/10.1016/j.ijin.2023.02.001>
- Dehghan Rouzi, M.; Moshiri, B.; Khoshnevisan, M.; Akhaee, M.A.; Jaryani, F.; Salehi Nasab, S.; Lee, M. Breast Cancer Detection with an Ensemble of Deep Learning Networks Using a Consensus-Adaptive Weighting Method. *J. Imaging* 2023, 9, 247. <https://doi.org/10.3390/jimaging911024>
- Breast Cancer Detection Using Deep Learning Technique Based on Ultrasound Image link: <https://arxiv.org/pdf/2312.05261>
- Breast Cancer Detection Using Deep Learning: An Investigation Using the DDSM Received 31 July 2023, accepted 28 August 2023, date of publication 4 September 2023, date of current version 9 October 2023. Digital

Object Identifier 10.1109/ACCESS.2023.3311892Dataset and a Customized AlexNet and Support Vector Machine <https://ieeexplore.ieee.org/stamp/stamp.jsp?arnumber=10239136>

Prema Kumar Medapati Breast Cancer Detection Using Deep Learning

DOI:10.1109/INCET61516.2024.10593400 link:

https://www.researchgate.net/publication/382619554_Breast_Cancer_Detection_Using_Deep_Learning

Shahzad Ahmad Qureshi Breast Cancer Detection using Mammography: Image Processing to Deep LearningDOI:10.20944/preprints 202405.0527.v1 link:

https://www.researchgate.net/publication/380600386_Breast_Cancer_Detection_using_Mammography_Image_Processing_to_Deep_Learning