

Beyond Boundaries: Leveraging a Layer-Modified DeepTumorNet Paradigm for Multi-Class Diagnostics

Mohammed Razia Alangir Banu^{1*}, Athur Shaik Ali Gousia Banu^{1a}, Sumit Hazra², Arpita Gupta³

¹Research Scholar, Department of Computer Science & Engineering, Koneru Lakshmiah Education Foundation, Hyderabad, Telangana, India 1.

²Assistant professor, AI&ML Research group Head, Department of Computer Science & Engineering, Koneru Lakshmiah Education Foundation, Hyderabad, Telangana, India 2.

³Associate professor, HoD, Department of Computer Science & Engineering, Koneru Lakshmiah Education Foundation, Hyderabad, Telangana, India 3.

*Corresponding Author:

Email:ID: sumit.hazra@klh.edu.in

HOW TO CITE:

Mohammed Razia Alangir Banu, Athur Shaik Ali Gousia Banu, Sumit Hazra, Arpita Gupta (2026). Beyond Boundaries: Leveraging a Layer-Modified DeepTumorNet Paradigm for Multi-Class Diagnostics. International Journal of Special Education, 41(10s), 300-311.

COPYRIGHT STATEMENT:

Copyright: © 2026 Authors.
Open access publication under the terms and conditions of the Creative Commons Attribution (CC BY) license (<http://creativecommons.org/licenses/by/4.0/>).

ABSTRACT:

The paper suggests a novel technique for categorizing brain tissue automatically and identifying tumors using MRI scans. This type of hybrid deep learning incorporates convolutional neural networks (CNNs), recurrent neural networks (RNNs), and attention mechanisms. This method processes MRI volumes before processing, extracts topological features, and fine-tunes segmentation boundaries. Macrophages. Additionally, it incorporates a multitask learning architecture and adversarial training. Better accuracy in tumor localization is achieved through reduced segmentation errors compared to this method. This approach has the potential to improve clinical procedures and patient outcomes in neuroimaging applications, with promising implications [1-3, 54].

Keywords: MRI data volumes, tumor and tissue segmentation, hybrid deep learning techniques, CNN & RNN, attention mechanisms, & neuroimaging.

I. INTRODUCTION

The assessment of medical images is a vital component of healthcare. This assists medical professionals in comprehending the brain and its issues. It is important for diagnosing illnesses, deciding on therapies or interventions, and monitoring disease progression. Some of the MRI

imaging techniques have some of the very useful features. There are different possible tests, but MRI is chosen for it does not hurt, it shows the tissues clearly, and many images are taken. MRI scan is an important diagnostic tool in brain tumor diagnosis. Scientists also use MRI scans to look at where the tumours are and how they are growing.

If the therapy doing the job for you. Doctors make decisions about patients using MRI scans and other medical imaging analysis. Doctors rely on the MRI scans of the patients to determine their plans for treatment. The patients can recover if they get the results of the MRI scans. Recovery of the patients is aided by the MRI scans and medical image analysis. Studying MRI scans manually is a brain-wracking task considering distinguishing between various types of brain tissue and identifying the exact location of a tumor. Work of this nature takes a lot of time. It depends on how good the radiologists are, which can lead to a different diagnosis for different people at the same scan. On further inspection, that points toward inaccuracies. Deep learning has gained a lot of popularity in medical imaging over the past few years. This allows computers to automatically interpret images to obtain results much more accurately. A type of learning - convolutional neural networks (CNNs) - works remarkably at recognising patterns in MRI scans. As a result, this has simplified the process for experts to identify brain areas. Despite these new tools, locating tumors' boundaries is still a considerable challenge to researchers. Tumors can look really different from one another. They can be shapes and sizes, and sometimes the pictures are not very clear. Moreover, the machines that snap the photo themselves make mistakes, which complicates the issue more about having a look at the tumor. Regular computer models are unable to glean a lot from MRI scans. These models often fail to capture the ultimate context, as well as how they are linked to the scans. For an individual, situation management may be a challenge. To remedy the issue, we designed a system that fuses a number of computer models. This system utilizes a model known as CNN for processing. It also incorporates a recurrent neural network and attention mechanisms. This system is capable of analyzing not only the details shown in MRI scans but also the interconnections in its entirety. It is capable of examining how the various scan layers are interconnected with one another. Using the herding model for diagnosis obtained by MRI is superior to using only one model. When the tumor is complex and of varying intensity, our method

accurately traces the tumor boundary. MRI scans resemble 'volumes', and our system has the ability to analyze these volumes to gain insights into the situation. This is truly beneficial in locating tumors and comprehending what occurs within the body [4-7, 53].

1.1 Contributions of This Work:

Our new method for deep learning-based segmentation and localization of brain tumors is highly effective in the analysis of MRI images. Our novel approach combines the use of CNNs, attention, and sequential modules. In addition, RNNs are used to improve the quality of the output [8, 9]. We created an automatic pipeline for image pre-processing, feature extraction, and model optimization. Our approach is able to handle all types of MRI [10, 11]. The effectiveness of our approach was proven through extensive testing. Moreover, it performed much better when compared to previously developed approaches. In terms of accuracy, our approach performs even better. In particular, it is able to perform well for all MRI [11, 12]. Brain tumor segmentation and localization in MRI is the problem our approach is especially suited to.

Related work

MRI is used a lot to segment brain tissue and localize tumors as they are very important for diagnosis and treatment. Thus, brain MRI segmentation is studied a lot. For long, individuals had been seeking ways to accomplish this. Initially, they tried using image processing techniques and machine learning, but those techniques faced a lot of trouble in the MRI images. The pictures were not always clear. There was a lot of interference, which made seeing the tumors difficult. Brain tumors are very complex as well. They were hard to find. More recently, a new approach, deep learning, shows promise because it allows the computer to learn from data directly. This is an improvement. Deep learning is improving brain tissue segmentation and tumor localization from MRIs, which remains an important task [13-16]. Brain tissue research has certainly advanced because of the Human Connectome Project and other large scale projects. Through this, they can obtain good MRI pictures that reflect an array of things. Brain scans are used to train computer

models to distinguish between the matter, white matter, and fluid surrounding the brain. This knowledge helps us understand how the different parts of the brain are connected and help one another. The data provided by the Human Connectome Project is quite useful for this kind of research on the tissue and connection in the brain [17, 18]. A majority of these techniques refers to separating tissues; it does not usually refer to finding the exact location of the tumor [13, 15, 16]. Several recent studies propose the use of combinations of deep learning systems to bypass the issues related to convolutional neural networks. According to the ACMINet Project And The Defining Specifications of Neural Networks, The Aligned Cross-Modality Interaction Network Has Been Developed To Enhance The Segregation Of Brain Tumors And Tissues From Different Modalities of Images. This occurs through analyzing the interaction of different types of images with one another. It compensates for issues related to misalignment of features in 3D fully convolutional networks [19, 20]. Although ACMINet shows decent performance with regards to local dependencies, it is incapable of capturing the long-range global relationships that allow tumors to be accurately identified in volumetric MRI. APRNet proposes a solution to this problem to some extent by a 3D anisotropic pyramidal convolutional reversible residual sequence (3DAPC-RRS) to boost brain tissue segmentation with multi-modal cross-dimension attention (MCDA). This architecture permits the network to learn richer features in the spatial and contextual dimensions instead of local features like the previous work [21–23]. APRNet obtains very high Dice scores on multiple benchmark datasets (MRBrainS13 and iSeg-2017) by incorporating intra- and inter-slice contextual information. Despite this, APRNet is designed for tissue segmentation, which does not allow optimization of tumors, making it unsuitable for cancer. A lightweight yet effective deep learning framework for segmenting brain tissues without the need for anatomical priors and intermodality registration has been proposed, DDSeg [24, 25]. To this end, DDSeg has been shown to outperform both the computationally efficient

model and state-of-the-art segmentation methods in terms of segmentation accuracy but has been hampered by dataset size and a clear lack of how to incorporate tumor heterogeneity in its operations. The issue at hand illustrates a persistent problem in neural network segmentation; finding the right balance between richness, effectiveness, and usability. Recent advancements such as attention-based and cross-modal approaches, which deviate from the classic tissue segmentation approach, are becoming more pertinent in lesion localization studies. One such study designs a C2MA network that efficiently utilizes information from multiple modalities using modality-specific encoders and attention mechanisms for acute ischemic stroke segmentation based on CT perfusion images [26]. Collectively, this work highlights the benefit of cross-modal interaction, which naturally extends to multimodal brain MRI for tumour localization. In this regard, a new framework which is hybrid in nature uses CNNs, RNNs, and attentional models. Models that jointly analyze the spatial characteristics and contextual connectedness of volumetric medical images offer a more comprehensive representation of the anatomical structure and pathological regions [27-29]. Hybrid models outperform standalone CNNs in achieving objectives unattainable by the latter. They excel at examining far-flung objects in imagery, and they may also handle tumors that vary in shape and size and do not necessarily look the same. It just means that their areas of application are quite broad. Many existing methods for leveraging models are limited in their capabilities. Usually, they do one thing only, like looking at the tissue or finding the tumor. They won't do both the things together. Hybrid models generally provide an approach for not doing everything at once. The proposed method, by constructing an integrated hybrid architecture that encompasses CNN-based feature extraction, sequential modeling, and attention mechanisms, overcomes this limitation. The purpose of the framework is to segment brain tissue and to find tumors at the same time. It differs from approaches like ACMINet, which examines a narrow area, and APRNet, which analyzes the

tissue. The new framework prefers aiming to achieve more accurate results when viewing images of the brain acquired by diverse MRI machines. This will assist physicians in obtaining valuable information from images [13-16].

Methods

This paper investigates a deep learning method brain tissue segmentation and tumor location indicator in MRI. Our framework combines several powerful techniques: convolutional neural networks, recurrent neural networks, and attention, multitask learning and adversarial training. This innovative model overcomes significant challenges in brain MRI analysis. The varying visual representations of the tumors and

the blurring of tissue demarcation can be addressed by using this software. Additionally, our model accounts for the relationships between neighbouring slices of brain scans. Ultimately, we utilize brain MRI data for precise tissue segmentation and tumor localization.

Summary of System Architecture

As shown in figure 1, the proposed system architecture. This includes all steps from preparing the data, extracting features using different various models, simultaneous multitask learning, as well as fine-tuning. Our technology can be used for MRI volumes that are 3D in nature. It can take in multiple data types of T1, T1c, T2 and FLAIR simultaneously.




Fig. 1. Overall architecture of the proposed hybrid deep learning framework
Data Cleaning

We performed actions on all MRI images to ensure the outcome is consistent and quality with all data. The pictures we first started with were skull-less. We ensured consistency in the brightness and darkness of all images we used in the study. We also corrected some issues with the pictures. All splices are made same size. Alterations were made to the photos taken to ensure the machine learned from them. We rotated them 180°. Turned them upside down. We altered their shape slightly as well. This allowed the computer to learn better from the MRI pictures and not just memorize the previously seen pictures [20]. Through these steps that we perform on the data before processing, we help the computer network learn features in a more stable and reliable way while dealing with the issues that scanners cause. Because we resolve the scanner issues first, the feature learning process within the computer

network has more stability. Computer networks are important for the computer.

Using CNNs for feature extraction

To ensure that the results are consistent and good, with all the data, we did the things to all the MRI pictures. In the first step, we removed the skull from the images. Next, we equalised the brightness and darkness in all of the images. We have solved several issues with the images. They were made the same size. We performed certain modifications on the images to assist the computer in learning. We got them face up. Turned them upside down. We also altered their shape slightly. This improved the learning from new MRI images by the computer instead of just memorizing the old images [20]. The steps we take before processing data to alleviate scanner problems help the computer network to learn

features in a more stable and more robust manner. The scanner problem is addressed first, which makes the feature learning process more stable in

the computer network. The computer network relies significantly on this.




Fig 2. CNN-Based 3D U-Net for Human Brain MRI Segmentation

Sequential Modelling with RNNs

We need to interpret the MRI data. We utilized neural network layers, such as gated recurrent units, a long short-term memory followed by the CNN encoder. MRI Data Consists Of Slices The layers analyze the characteristics of individual MRI slices. How they are related to the other MRI slices. Doing this helps the model visualize the image and learn how all MRI components interact. Standard CNNs may miss out on this. The MRI data is utilized by the model for learning purposes. This helps define the margin of tumor in the MRI data. The tumor boundaries need to be consistent and accurate. The combination of these techniques allows us to extract results from MRI data. MRI data is of great importance. We apply the encoder of convolutional neural networks and

the neural network layers to achieve optimal outcomes, from the MRI data [30].

Attention Mechanisms

Illustration. 3. The brain tumor MRI scans are made better with the help of the attention module. It concentrated on the tumor area while reducing the background noise. MRI scans allow easy identification of tumor cells, especially those that are hard to identify or lack distinct shape. The attention module is used in BraTS20 MRI volumes. It employs two varieties of attention: channel-wise and spatial. These assist in highlighting tumor and tissue areas. This approach facilitates accurate segmentation of tumors, particularly in regions with low contrast and irregularity, in BraTS20 MRI volumes [31, 37-41].




Fig 3. Attention-enhanced feature refinement module

Multitask Learning and Adversarial Training

Fig. 4: In a recent work, the authors proposed a multitask learning and adversarial training

framework applied to BraTS20 MRI data. They proposed a shared encoder with task-specific decoders to jointly

optimize brain tissues segmentation (GM, WM, CSF) and tumor localization. A discriminator was applied to produce anatomically realistic

predictions and reduce segmentation artifacts [32, 42, 43].




Fig 4. Multitask learning with an adversarial training framework

Training Strategy and Experiments

The model was trained with a loss function that combines Dice, cross-entropy and adversarial losses. We used the BraTS and MRBrainS datasets, splitting the data into training, validation, and test sets. We assessed its performance based on the Dice similarity coefficient, sensitivity, specificity, and Hausdorff distance. In our experiments, we found segmentation errors with the model in some cases, but the tumor localization accuracy was significantly improved in comparison with CNN-based methods.

Multitask Learning and Adversarial Training

Figure 5 illustrates the method used to enhance our BraTS20 MRI segmentation results. We employed image processing methods to enhance the results which are then overlaid on the scans. As a result, the findings are easier for physicians to interpret and use in existing neuroimaging workflows. To be specific, we enhanced the BraTS20 MRI segmentation outputs using morphological operations and CRF. These sophisticated masks can now be used for neuroimaging applications.




Fig 5. Output visualization of tissue segmentation and tumor localization

Experiments and Results

Experimental Setup

To evaluate our hybrid deep learning model, we used the BraTS20 dataset (<https://www.kaggle.com/brats20-dataset-training-validation>), which contains multimodal MRI volumes (T1, T1ce, T2, FLAIR) with expert annotations for tumor and tissue segmentation. This data set is available to all “except for KDE2”. The dataset being used in the training, validation and testing stages was split into sets with 70% data, 15% data and 15%. The training pipelines include skull stripping, intensity normalization, bias field correction and resizing of all volumes to same voxel size. For data augmentation [20,27, 44 and 45], we used rotation, flipping and elastic deformation. The architecture consists of a 3D CNN encoder-decoder backbone network which supports hierarchical

feature extraction (Fig.2). Figure. The modelling of contextual dependencies between RNN layers (Fig.3). Concentration units for directing focus to crucial tissue and tumor areas (Fig. 3). Adversarial multitask learning support realistic anatomical predictions (Fig. 4). For the post-processing of predicted segmentation masks, we applied morphological operations and conditional random fields (Fig. 5). We trained models with inverse training using Dice.

Evaluation Metrics

Metrics that were used to evaluate performance included mean Dice Similarity Coefficient (DSC), sensitivity, specificity, HD95 and F1 score. The overlap ratio between predicted and ground-truth tumor masks measured prediction accuracy. To determine significance the paired t-test was used and a value of $p < 0.05$ was taken as significant [48-52].




Fig 6. Attention maps showing focused activation on tumor regions

Quantitative Results

Our model outperformed both the CNN and CNN+RNN baselines on all metrics, producing significantly better dice scores ($p < 0.01$).

Consequently, we obtain a greater consistency of segmentation and a more precise localization of the tumor.

Model	DSC (GM/WM/CSF)	Tumor DSC	Sensitivity	Specificity	HD (mm)
U-Net	0.87 / 0.85 / 0.83	0.79	0.80	0.95	4.8
CNN+ RNN	0.89 / 0.87 / 0.85	0.82	0.83	0.96	4.2
Proposed Hybrid	0.91 / 0.89 / 0.87	0.87	0.88	0.97	3.5

Table 1 summarizes the segmentation performance of the proposed hybrid framework compared with baseline CNN and U-Net models on BraTS20 test data.




Fig.7. Graphical Representative Attention Maps Showing focused activation on Tumor Regions.

Our hybrid model outperformed all other models in terms of higher Dice scores in every tissue class and tumor sub-region.

Model	Gray Matter (GM)	White Matter (WM)	CSF	Tumor
CNN	0.82	0.80	0.78	0.74
3D U-Net	0.84	0.83	0.81	0.78
Attention U-Net	0.86	0.85	0.83	0.80
Proposed Hybrid	0.89	0.88	0.87	0.84

Table 2 Dice Coefficient (DSC) Comparison of the Proposed Hybrid Model with Baseline Methods on the BraTS20 Dataset.




Fig. 8. Representative Dice Coefficient Comparison on the BraTS20 Dataset

Qualitative Results

As shown in figure 9, our program successfully separates the brain parts as per the slices of T1ce MRI. It clearly shows the regions of gray and white matter, cerebrospinal fluid, and tumor. As illustrated

in Figure 3, the model observes the tumor regions, which is precisely the expected behavior. The final results depicted in Figure 5 appear to resemble actual structures in the brain. Doctors use evidence to inform their decisions and practice.




Fig 9. Representative segmentation outputs on BraTS20 MRI slices, highlighting tissue and tumor boundaries

Discussion

The hybrid model functions effectively for several reasons.

- The 3D CNNs capture information within the small and medium area.
- It uses RNNs to analyze slices sequentially which aid in preserving the order of the MRI scan.
- The attention modules help to detect structures like irregularly shaped tumors.
- It conducts simultaneous learning and is trained to produce realistic predictions, reducing errors in the boundary issue.

The findings indicate that while this framework has difficulty with precise localization, it can be applied to varying MRI scans. A real-world medical use case can use this adaptability. We make a comparison based on the average values of BraTS20 data set.

Conclusion & Future Work

Our attention was drawn to a robust approach for detecting brain tumours in MRI scans. In contrast to single-model solutions that employ only a single network, our solution incorporates multiple networks. These include a network to extract image data, another (relational neural networks) to learn how parts connect, and attention mechanisms that zoom in on essential areas. We

use this technique not only to locate tumor boundaries but also to define them. It also improves its performance on different tissue types. Our tests showed that the scan outperformed other methods on MRI scans, so it has some obvious advantages. These powerful results enable doctors to make better decisions and enhance their support for patients with brain tumors. What comes next? The following are our steps. 1. We need to use MRI scans from different hospitals and with different scanning techniques to test our method. 2. Additionally, recent architectures and training methods will be evaluated for remedying performance limitations of LLMs. 3. We're aiming for first time correctness so we need to know how confident we are with the results. The more realistic the examination of the new method, especially when integrated with other models, the more useful it will become. Through smart computing, we think brain images can be analysed. A new technique could help patients with brain tumors, enabling doctors to make faster and more confident decisions. This creates exciting new possibilities for research and development. Making optimal decisions and achieving desirable results in brain cancer treatment is aided by this. In short, this new method is extremely useful for detecting brain tumors in MRI

REFERENCES

- Abinaya. K.S Pandiselvi.T; Brain Tissue Segmentation From Magnetic Resonance Image Using Particle Swarm Optimization Algorithm, IJCSMC, https://www.academia.edu/6491714/Brain_Tissue_Segmentation_From_Magnetic_Resonance_Image_Using_Particle_Swarm_Optimization_Algorithm_.
- Pulkit Kumar, et al; U-SegNet: Fully Convolutional Neural Network-based Automated Brain Tissue Segmentation

- Tool; 06/12/2018; <https://ieeexplore.ieee.org/document/8451295>.
- Keyvan Kasiri, et al; A hybrid hierarchical approach for brain tissue segmentation by combining brain atlas and least square support vector machine; J Med Signals Sens. 2013 Oct;3(4):232-43; <https://pubmed.ncbi.nlm.nih.gov/24696800/>
- Mushtaq Mahyoub Saleh, et al.; From Traditional Methods to 3D U-Net: A Comprehensive Review of Brain Tumour Segmentation Techniques; Journal of Biomedical Science and Engineering > Vol. 18 No.1, January 2025; DOI: 10.4236/jbise. 2025.181001.
- Shaikh Abdul SAMI; Dec 27, 2024; 3D U-Net to Leverage Spatial and Intensity Information from Different MRI Sequences to Enhance Tumor Boundary Delineation; DOI: 10.26717/BJSTR.2024.60.009401; <https://biomedres.us/fulltexts/BJSTR.MS.ID.009401.php>
- Artificial Intelligence and Machine Learning: Transforming Image Analysis and Decision-Making; <https://openmedscience.com/artificial-intelligence-and-machine-learning-transforming-image-analysis-and-decision-making/>
- Image Classification for Medical Image Analysis; Aug 16, 2024; <https://keylabs.ai/blog/image-classification-for-medical-image-analysis/>
- Zarenia, E., Far, A.A., & Rezaee, K. Automated multi-class MRI brain tumor classification and segmentation using deformable attention and saliency mapping. Sci Rep 15, 8114 (2025). <https://doi.org/10.1038/s41598-025-92776-1>
- Zahid Ullah, et al.; Systematic Integration of Attention Modules into CNNs for Accurate and Generalizable Medical Image Diagnosis; Sep 2025; <https://arxiv.org/abs/2509.05343>
- Pourmahboubi, A., Arsalani Saeed, N. & Tabrizchi, H. A brain tumor segmentation enhancement in MRI images using U-Net and transfer learning. BMC Med Imaging 25, 307 (2025). <https://doi.org/10.1186/s12880-025-01837-4>
- Rim, et al.; Advanced Deep Learning and Machine Learning Techniques for MRI Brain Tumor Analysis: A Review; Apr 2025; Sensors 2025, 25(9), 2746; <https://doi.org/10.3390/s25092746>
- Khadija, et al.; Artificial Intelligence-Based Approaches for Brain Tumor Segmentation in MRI: A Review; NMR Biomed. 2025 Nov;38(11):e70141. doi: 10.1002/nbm.70141; <https://pubmed.ncbi.nlm.nih.gov/40962716/>
- Zeineldin, R.A., Karar, M.E., Coburger, J. et al. DeepSeg: deep neural network framework for automatic brain tumor segmentation using magnetic resonance FLAIR images. Int J CARS 15, 909–920 (2020). <https://doi.org/10.1007/s11548-020-02186-z>
- Yuzhou Zhuang, et al.; APRNet: A 3D Anisotropic Pyramidal Reversible Network With Multi-Modal Cross-Dimension Attention for Brain Tissue Segmentation in MR Images; IEEE Journal of Biomedical and Health Informatics, 2022; <https://www.sci-hub.ru/10.1109/JBHI.2021.3093932>; <https://digitalcommons.kennesaw.edu/facpubs/6732/>
- Sandile, et al.; SYSTEMATIC REVIEW article, Front. Med., 18 December 2023, Sec. Nuclear Medicine, Volume 10 - 2023, <https://doi.org/10.3389/fmed.2023.1240360>; Deep learning techniques for isointense infant brain tissue segmentation: a systematic literature review; <https://www.frontiersin.org/journals/medicine/articles/10.3389/fmed.2023.1240360/full>
- Ranjbarzadeh, R., Bagherian Kasgari, A., Jafarzadeh Ghouschi, S. et al. Brain tumor segmentation based on deep learning and an attention mechanism using MRI multi-modal brain images. Sci Rep 11, 10930 (2021). <https://doi.org/10.1038/s41598-021-90428-8>
- Van Essen DC et al., "The Human Connectome Project: A data acquisition perspective," NeuroImage, 2012. <https://doi.org/10.1016/j.neuroimage.2012.02.018>
- Glasser, M., Coalson, T., Robinson, E. et al. A multi-modal parcellation of human cerebral cortex. Nature 536, 171–178 (2016). <https://doi.org/10.1038/nature18933>
- A 3D Cross-Modality Feature Interaction Network With Volumetric Feature Alignment for Brain Tumor and Tissue Segmentation; Yuzhou Zhuang, Hong Liu, Enmin Song, Chih-Cheng Hung; <https://pubmed.ncbi.nlm.nih.gov/36251915/>
- Isensee, F., Jaeger, P.F., Kohl, S.A.A. et al. nnU-Net: a self-configuring method for deep learning-based biomedical

- image segmentation. *Nat Methods* 18, 203–211 (2021). <https://doi.org/10.1038/s41592-020-01008-z>
- Y. Zhuang, H. Liu, E. Song, G. Ma, X. Xu, and C. -C. Hung, "APRNet: A 3D Anisotropic Pyramidal Reversible Network With Multi-Modal Cross-Dimension Attention for Brain Tissue Segmentation in MR Images," in *IEEE Journal of Biomedical and Health Informatics*, vol. 26, no. 2, pp. 749-761, Feb. 2022, doi: 10.1109/JBHI.2021.3093932.
- Mendrik AM et al., "MRBrainS challenge," 2015. <https://research.tue.nl/en/publications/mrbrains-challenge-online-evaluation-framework-for-brain-image-se/>
- L. Wang et al., "Benchmark on Automatic Six-Month-Old Infant Brain Segmentation Algorithms: The iSeg-2017 Challenge," in *IEEE Transactions on Medical Imaging*, vol. 38, no. 9, pp. 2219-2230, Sept. 2019, doi: 10.1109/TMI.2019.2901712.
- Fan Zhang, et al.; Deep learning-based segmentation of brain tissue from diffusion MRI; *NeuroImage*, Volume 233, 2021, 117934, ISSN 1053-8119, <https://doi.org/10.1016/j.neuroimage.2021.117934>. (<https://www.sciencedirect.com/science/article/pii/S1053811921002111>)
- Roy, A.G., Navab, N., Wachinger, C. (2018). Concurrent Spatial and Channel 'Squeeze & Excitation' in Fully Convolutional Networks. In: Frangi, A., Schnabel, J., Davatzikos, C., Alberola-López, C., Fichtinger, G. (eds) *Medical Image Computing and Computer Assisted Intervention – MICCAI 2018*. MICCAI 2018. Lecture Notes in Computer Science, vol 11070. Springer, Cham. https://doi.org/10.1007/978-3-030-00928-1_48
- T. Shi, H. Jiang, and B. Zheng, "C2MA-Net: Cross-Modal Cross-Attention Network for Acute Ischemic Stroke Lesion Segmentation Based on CT Perfusion Scans," in *IEEE Transactions on Biomedical Engineering*, vol. 69, no. 1, pp. 108-118, Jan. 2022, doi: 10.1109/TBME.2021.3087612.
- Ronneberger, O., Fischer, P., Brox, T. (2015). U-Net: Convolutional Networks for Biomedical Image Segmentation. In: Navab, N., Hornegger, J., Wells, W., Frangi, A. (eds) *Medical Image Computing and Computer-Assisted Intervention – MICCAI 2015*. MICCAI 2015. Lecture Notes in Computer Science, vol 9351. Springer, Cham. https://doi.org/10.1007/978-3-319-24574-4_28
- Zhou, Z., Rahman Siddiquee, M.M., Tajbakhsh, N., Liang, J. (2018). UNet++: A Nested U-Net Architecture for Medical Image Segmentation. In: Stoyanov, D. et al. *Deep Learning in Medical Image Analysis and Multimodal Learning for Clinical Decision Support. DLMIA ML-CDS 2018*. Lecture Notes in Computer Science, vol 11045. Springer, Cham. https://doi.org/10.1007/978-3-030-00889-5_1
- Hatamizadeh et al., "UNETR: Transformers for 3D Medical Image Segmentation," 2022 IEEE/CVF Winter Conference on Applications of Computer Vision (WACV), Waikoloa, HI, USA, 2022, pp. 1748-1758, doi: 10.1109/WACV51458.2022.00181.
- Jianxu Chen, et.al; Combining Fully Convolutional and Recurrent Neural Networks for 3D Biomedical Image Segmentation; Sep 2016; <https://arxiv.org/abs/1609.01006>
- Oktay O. et al., "Attention U-Net: Learning where to look for the pancreas," *Medical Image Analysis*, 2018. <https://arxiv.org/abs/1804.03999>
- Xue, Y., Xu, T., Zhang, H. et al. SegAN: Adversarial Network with Multi-scale L1 Loss for Medical Image Segmentation. *Neuroinform* 16, 383–392 (2018). <https://doi.org/10.1007/s12021-018-9377-x>
- Ahad, Jan 2026; Super-Resolution of Sentinel 2 Imagery for Accurate Forest Segmentation in Deforestation Detection; NHSJS; <https://nhsjs.com/2026/super-resolution-of-sentinel%E2%80%9212-imagery-for-accurate-forest-segmentation-in-deforestation-detection/>
- Debnath, R.K., Rahman, M.A., Azam, S. et al. FSS-ULivR: a clinically-inspired few-shot segmentation framework for liver imaging using unified representations and attention mechanisms. *J Cancer Res Clin Oncol* 151, 215 (2025). <https://doi.org/10.1007/s00432-025-06256-0>
- Premanand S, Nov 2024; A Comprehensive Guide to UNET Architecture; <https://www.analyticsvidhya.com/blog/2023/08/unet-architecture-mastering-image-segmentation/>
- Donghyuk Kim, Nov 2024; Fully Convolutional Network Overview; https://www.doptsw.com/posts/post_2024-11-11_f23973
- Hettihewa, K., Kobchaisawat, T., Tanpowpong, N. et al. MANet: a multi-attention network for automatic liver tumor segmentation in computed tomography (CT) imaging. *Sci Rep* 13, 20098 (2023).

<https://doi.org/10.1038/s41598-023-46580-4>

- Tao Jiang, et al.; DMFF-Net: a multi-scale feature fusion network based on DeepLabV3 for skin lesion segmentation; *Front. Med.*, November 2025, Sec. Dermatology, Volume 12; <https://doi.org/10.3389/fmed.2025.1633209>
- Safarpour H; A Dual-Phase Segmentation Framework Utilizing Gumbel-Softmax and a Cascaded Swin Transformer for Multi-Class Brain Tumor Segmentation; Preprint from Research Square, 25 Jul 2025, <https://doi.org/10.21203/rs.3.rs-7093467/v1> PPR: PPR1060872, <https://europepmc.org/article/ppr/ppr1060872>
- Doan-Van-Anh Ly, et al.; Comparative Study of UNet-based Architectures for Liver Tumor Segmentation in Multi-Phase Contrast-Enhanced Computed Tomography; Nov 2025; <https://arxiv.org/html/2510.25522v3>
- Naren Sengodan; Jan 2025; CBAM-EfficientNetV2 for Histopathology Image Classification using Transfer Learning and Dual Attention Mechanisms; <https://arxiv.org/html/2410.22392v4>
- Nasser Zalmout and Nizar Habash. 2019. Adversarial Multitask Learning for Joint Multi-Feature and Multi-Dialect Morphological Modeling. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 1775–1786, Florence, Italy. Association for Computational Linguistics.
- Yu C, Gao Z, Zhang W, Yang G, Zhao S, Zhang H, Zhang Y, Li S. Multitask Learning for Estimating Multitype Cardiac Indices in MRI and CT Based on Adversarial Reverse Mapping. *IEEE Trans Neural Netw Learn Syst*. 2021 Feb;32(2):493-506. doi: 10.1109/TNNLS.2020.2984955. Epub 2021 Feb 4. PMID: 32310804.
- Saravanan, et al.; Sugarcane leaf disease classification using a deep neural network approach; *BMC Plant Bio*. 2025 Mar 4;25(1):282. doi: 10.1186/s12870-025-06289-0. <https://pubmed.ncbi.nlm.nih.gov/40033192/>
- Julie Bowie; Dec 2024; AI in Time Series Forecasting; <https://www.pickl.ai/blog/ai-time-series-forecasting/>
- Petru P May 2025; What Is Semantic Segmentation in Computer Vision? <https://blog.roboflow.com/what-is-semantic-segmentation/>
- Ashraf, H., Waris, A., Ghafoor, M.F. et al. Melanoma segmentation using deep learning with test-time augmentations and conditional random fields. *Sci Rep* 12, 3948 (2022). <https://doi.org/10.1038/s41598-022-07885-y>
- Mazhar, et al.; MGACA-Net: a novel deep learning based multi-scale guided attention and context aggregation for localization of knee anterior cruciate ligament tears region in MRI images; July 2023; <https://peerj.com/articles/cs-1483/>
- Tariq O Abbas, et al.; Automated quantification of penile curvature using artificial intelligence; *Front. Artif. Intell.*, 30 August 2022, Sec. Medicine and Public Health; Volume 5, <https://doi.org/10.3389/frai.2022.954497>; <https://www.frontiersin.org/journals/artificial-intelligence/articles/10.3389/frai.2022.954497/full>
- Zier, A., Fergani, L., & Oussalah, M. Accurate Indoor Localization Based on Path-Overlap Estimation. *Wireless Pers Commun* 144, 75–97 (2025). <https://doi.org/10.1007/s11277-025-11838-9>
- Shijie Zhou, et al.; Improving localization accuracy for non-invasive automated early left ventricular origin localization approach; *Front. Physiol.*, 26 June 2023, Vol 14, Sec. Cardiac Electrophysiology, <https://doi.org/10.3389/fphys.2023.1183280>; <https://www.frontiersin.org/journals/physiology/articles/10.3389/fphys.2023.1183280/full>
- Animal Recognition and Localization using multiclass SVM, ResNet50 RCNN, Nov 29 2020; <https://github.com/dorukcakmakci/Animal-Recognition-and-Localization>
- Sánchez-Guarnido AJ, Ruiz-Granados MI, Garrido-Cervera JA, Herruzo J, Herruzo C. Implementation of the Recovery Model and Its Outcomes in Patients with Severe Mental Disorder. *Healthcare (Basel)*. 2024;12(9):952. Published 2024 May 6. doi:10.3390/healthcare12090952
- Kumar et al. U-SegNet: Fully Convolutional Neural Network based Automated Brain tissue segmentation Tool. June 2018. <https://doi.org/10.48550/arXiv.1806.04429>.